

Station No.	Distance	Bearing	Beaman or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
								1522.0	E 11/34
B5	310		+Z	1.5	-6.2	-4.7	1517.3		
	1650		BH	8.2	-8.3	-16.5		1500.8	Rd to E/W FNC
28	1500		BH	7.6	-7.5	-15.1		1502.2	
29	1170		BH	7.3	-5.9	-13.2		1504.1	
30	840		-	10.8				1506.5	
31	510		-	9.3				1508.1	
32	180		-	6.5				1510.8	
33	150		-	4.3				1513.1	
34	480		-	3.4				1513.9	
35	810		TH	3.8	+4.1	+0.3		1517.6	
36	1140		TH	1.9	+5.7	+3.8		1521.1	⊙
B5	1820		TH	9.1	-9.4	+0.3	1521.1		⊙
37	1485		TH	7.2	+7.4	-0.2		1520.6	
38	1155		-	1.1				1520.9	
39	825		-	4.5				1516.6	
40	495		-	7.3				1513.8	
N.E.	300		-	8.4				1512.7	T Rd to E. 1513.0
41	165		-	7.0				1514.1	N. Edge Rd to W
42	165		-	4.5				1516.6	
43	495		-	5.5				1515.6	BR
44	825		-	4.2				1516.2	

Station No.	Distance	Bearing	Beam or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
							1521.1'		
45	1155	-	-	1.9'		-1.9'		1519.2'	
46	1485		TH	5.3'	+7.4'	+2.1'		1521.3'	
47	1815		TH	4.3'	+9.1'	+4.9'		1526.6'	⊙
BS	495	-	-	6.8'		+6.8'	1532.8'		⊙
AB	165	-	-	3.9'				1528.9'	
49	165	-	-	5.1'				1537.9'	
50	495	-	-	11.7'				1521.1'	
51	825	-	-	14.9'				1517.9'	BR.
52	1155	-	-	12.3'				1520.5'	
53	1485	-	-	8.3'				1524.5'	
54	1815	-	-	5.8'				1527.0'	
RT			TH	12.1'					⊙
55	2145		TH	12.1'	+10.7'	-1.4'		1531.4'	⊙ S' S. of Rd. T. to W
BS	1980	-	-	8.4'	+19.8'	+22.3'	1559.6'		⊙ 1558.3' CORR H.I
56	1650	-	-	7.3'	-16.5'	-23.8'		1535.8'	
TR	1460		BH	13.0'	-7.3'	-20.3'		1539.3'	T. Rd. to E. 1538.0'
57	1320		BH	12.4'	-6.6'	-19.9'		1539.3'	
58	990		BH	12.4'	-5.9'	-17.6'		1540.7'	
59	660	-	-	1.3'				1545.9'	
60	330	-	-	9.0'				1549.3'	
61	0		BH	4.0'				1554.3'	

Station No.	Distance	Bearing	Beaman or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
							1558.31		
62	330		-	7.81				1550.51	
63	660		-	8.91				1549.41	
64	990		-	7.61				1550.71	
65	1320		-	7.81				1550.51	> Irrig. Well - E.
66	1650		-	6.91	-6.91			1551.41	
TR.5	2090		BH	7.11	+10.51	+17.61	1569.01		
67	1760		BH	7.51	-8.81	-16.31		1552.71	
68	1430		BH	8.61	-7.21	-15.81		1553.21	
69	1100		BH	10.41	-5.51	-15.91		1553.11	
70	770		-	14.61				1554.41	
71	440		-	9.21				1559.81	
72	110		-	8.61				1560.41	Well E
72	0	-	-	4.21	-4.01			1565.01	Rd T" 1564.91
73	220		-	6.31				1562.71	
74	560		-	7.31				1561.71	
74 1/2	590		BH	7.11	-3.91	-10.11		1558.91	74 1/2
75	890		-	3.91				1565.61	
75 1/2	920		-	4.21				1564.81	75 1/2
76	1220		TH	5.91	+6.11	+10.21		1569.21	76 1/2
77	1550		TH	8.91	+7.81	-1.11		1567.91	77 1/2
TR.5	1320		-	5.61	+5.61	1573.51			

Station No.	Distance	Bearing	Beam or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
							1573.5/		
78	990		-	3.5/				1570.0/	
79	660		-	4.4/				1568.9/	
80	330		-	4.1/				1569.4/	
TRI	190		-	3.8/				1569.7/	T. Rd. 1569.7/
81	0		-	4.0/				1569.5/	Rd Junct. in doubt ↑
82	330		-	7.2/				1566.3/	
83	660		-	9.8/				1563.7/	
84	990		-	12.5/				1561.0/	
85	1320		BH	8.8/-6.6/	-7.5/			1558.1/	
86	1650		-	12.7/	-12.7/			1561.2/	⊙ Hse to E 350'
85	1320		+1	5.7/-13.7/	-7.5/	1553.7/			1552.4/ CORR. H.I.
87	990		TH	2.9/+5.0/	+2.1/			1555.8/	Hse
88	660		-	1.8/				1551.9/	
R/T	600		-	1.1/				1552.6/	Rd T 1551.0/
89	330		-	1.9/				1550.2/	
90	0		-	4.0/				1548.1/	
91	330		-	10.7/				1547.0/	
92	660		-	14.8/				1537.2/	
93	990		BH	12.2/-5.0/	-17.2/			1534.9/	
94	1320		BH	11.6/-6.6/	-18.2/			1533.7/	
95	1650		BH	12.0/-8.3/	-20.3/			1531.8/	

Station No.	Distance	Bearing	Beaman or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
							1552.1		
96	1980		BH	9.9	-9.9	-19.8		1532.3	OFF RATE
BS	1320		+1	5.9	+13.2	+8.3	1524.0		π
97	990		TH	4.0	+5.0	+1.0		1525.0	
98	660		-	3.1				1520.9	
99	330		-	4.0				1520.9	
100	0		-	4.0				1520.9	
101	330		-	11.0				1513.9	
102	660		BH	12.3	-3.3	-15.6		1508.4	
103	990		BH	12.0	-5.0	-17.0		1507.0	
104	1320								
Rd T	1270		BH	9.5	-6.4	-15.9		1508.4	Rd T. 1508.9
104	1320		BH	9.7	-6.6	-16.3		1507.7	
105	1650		BH	9.5	-8.3	-17.8		1506.3	
106	1980		-	11.6				1512.4	
107	2310		-	10.8		-10.8		1513.3	○
BS	1460		+1	2.6	+14.6	+12.0	1501.2		π
108	1130		+1	2.8	+5.7	+2.9		1504.1	
109	800		-	9.3				1491.9	Use from E
110	490		-	13.4				1487.8	on Bridge - <u>Weak</u>
111	220		-	6.5				1494.3	
112	130		-	4.7				1496.5	

Station No.	Distance	Bearing	Beaman or Angle	Rod Reading	Product	Difference Elevation	H. I.	Elevation	REMARKS
							1501.2/		
113	460		-	1.9/				1499.3/	
114	790		-	1.9/				1499.3/	
115	1170		-	1.8/		-1.8/		1499.4/	○
* B3	85 990		-	6.1/		+6.1/	1505.5/		^
116	660		-	6.1/				1499.4/	
117	330		-	5.3/				1500.3/	
118	0		-	4.4/				1501.5/	
119	330		-	5.0/				1500.5/	F.O.L.
	570		-	4.2/		-4.2/		1501.3/	Rd "T" 1504.0/